

# RAUFILAM SLIDETEC SOFT

## Feel the difference.

### Properties

- Exclusive hose surface with **easy slide technology** for an unparalleled feel and convenient handling
- **Exceptionally** high flexibility
- Made of high-quality **environmentally friendly and physiologically harmless** PVC materials
- High resistance against chemicals (see material data sheet RAU-PVC AV0010)
- Abrasion-resistant and non-ageing
- High reinforcement density
- Temperature resistance  $-20^{\circ}\text{C}$  up to  $+60^{\circ}\text{C}$



### Inspections / standards

- **RoHS** 2011/65/EU
- **REACH** regulation (EC) no. 1907/2006 (no SVHC)
- End-of-life vehicle directive 2000/53/EC and 2002/525/EC
- RoHS electrical and electronic equipment directive 2011/65/EU as well as 2003/11/EC
- WEEE waste electrical and electronic equipment directive 2012/19/EU

### Material and colour

Inner layer: RAU-PVC 7005, black  
 Pressure carrier made of high-quality polyester fabric  
 Sheathing: RAU-PVC 6558, sky blue RAL5015

### Application

Compressed air supply for pneumatic tools  
 Fixed or mobile winding devices for compressed air supply

### Use

- Assembly companies
- Repair workshops (passenger vehicles/commercial vehicles)
- Joineries

Material no.	Internal Ø	Wall thickness	Permissible operating pressure bar (at 20°C)	Bending radius mm (at 20°C)	Coil length m	Packaging unit		EAN code
	mm	mm				metres/box	metres/pallet	
10290331001	6.0	2.5	20	35	50	250	3,000	4007360591281
10290341001	8.0	2.5	20	40	50	200	2,400	4007360591298
10290351001	9.0	2.8	20	45	50	150	1,800	4007360591809
10290361001	10.0	3.0	20	50	50	150	1,800	4007360591816
10290371001	12.7	3.0	20	60	50	100	1,200	4007360591823
10290661001	16.0	3.3	20	95	50	-	500	4007360635473
10290471001	19.4	3.7	20	130	50	-	500	4007360604233
10290531001	25.4	4.3	20	200	50	-	250	4007360604240

Can be supplied on reels compatible with the REHAU hose centre:

Material no.	Internal Ø	Wall thickness	Permissible operating pressure bar (at 20°C)	Bending radius mm (at 20°C)	Spool length m	Packaging unit	EAN code
	mm	mm				Spool	
10290331200	6.0	2.5	20	35	50	1	4007360605483
10290351200	9.0	2.8	20	45	40	1	4007360605490
10290371200	12.7	3.0	20	60	25	1	4007360606107

Please consult our technical delivery specification 11T/100 for further technical information.