

Hose made of spiral EVA, unreinforced, for extraction of air, dust, welding fumes and gases.



 SMOOTH SURFACE **

 FLEXIBILITY ****

 ABRASION RESISTANCE ***

 TEMPERATURE RANGE -30 °c 60 °c

 CHEMICAL RESISTANCE EVA Table

 CRUSHING RESISTANCE **

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H ₂ O	bending radius mm	total thickness mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	32.5	5	66	4	4.6	left	200	30	In stock
29		29	36	5	76	3.5	4.3	left	210	30	In stock
32	1 1/4	32	40.4	5	82	4.5	4.7	left	280	30	In stock
38	1 1/2	38	48	5	93	5	5.3	left	380	30	In stock
45	1 3/4	45	55	5	110	5	5.5	left	450	30	In stock
50	2	50	61	5	122	5.5	5.7	left	550	30	In stock
60		60	72	4	146	6	5.7	left	700	30	In stock
75		75	88.5	4	155	6.5	6.5	left	920	15	In stock
80		80	93	4	170	7	6.5	left	980	15	In stock